

PRODUCT Information

P.B. 177 • N-1601 Fredrikstad • Norway
+47 69 36 43 00 • Fax: +47 69 32 94 33
salg@mascot.no • www.mascot.no

MODEL 9581

AC/DC UNREGULATED PLUG-IN ADAPTER

- Max 3,6 W output power
- 230 VAC input voltage
- Available with EU and UK terminals
- Compliance with relevant worldwide safety standards
- Exchangeable output plugs, providing:
 - reduced stocking requirements
 - short delivery lead times
 - snap-locks for added safety



Technical Specifications

		9 V	12 V
Input voltage:	VAC	230 VAC $\pm$ 10%, 50 Hz	
Output voltage: <i>I_{out}</i> =max load	VDC	9 $\pm$ 5%	12 $\pm$ 5%
Max No load output voltage:	VDC	UK: 17, EU: 19	UK: 24, EU: 25
Max. Output power:	W	2,7	3,6
Max. Load current:	mA	300	
Temperature range:	°C	-10°C to +40°C	-10°C to +40°C
Protection:		Thermal fuse in primary	
Insulation class:		II	
Electrical safety		EN 60950	
EMC, Emission		EN50081-1	
EMC, Immunity		EN50082-1	
Mains connections:		EU and UK	
Output terminals:		Secondary cable	
IP-grade:		40	
Dimensions UK (LxWxH):	mm	59x51x47 (without pins)	
Dimensions EU (LxWxH):	mm	56x44x37 (without plug)	
Weight:	g	UK: 230, EU: 200	

EXCHANGEABLE OUTPUT PLUGS

With snap-locks



For added safety
both plug ends are clearly
marked to connect desired polarity

With reservations against misprint and changes in product specifications

pi9581J-e / 140301 / s.1/1

Mascot UK
P.O. Box 1560, Andover
SP11 8QZ HAMPSHIRE
UK
Phone: +44 (0)1264 357177
Fax: +44 (0)1264 364055

Mascot Deutschland
Mooshaldenweg 5
D-88069 TETTANANG
Germany
Phone: +49 7542 953540
Fax: +49 7542 953560

Mascot AS - Succursale France
23 Clos du Perthuis
F-14200 HEROUVILLE ST. CLAIR
France
Phone: +33 (0)2 31 06 04 40
Fax: +33 (0)2 31 06 04 50

Mascot Benelux
Wilderstraat 52
B-9400 APPELTERRE
Belgium
Phone: +32 (0) 54 600 442
Phone: +32 (0) 54 600 443

Mascot AS - Swedish Office
Phone: +46 (0) 526 14025
Fax: +46 (0) 526 15513